## Harlequin

## Flexity<sup>TM</sup>

**Harlequin Flexity** is a self-install sprung floor system featuring stained birch plywood panels and shock-dampening single density elastomer pads.


**Performance surface:** Harlequin Flexity can be used with a variety of performance surface options from the Harlequin range of performance vinyls and solid or engineered wood finishes. Ramps are available if required.

**Installation:** Harlequin Flexity is designed for permanent or semi-permanent installation. The panels join using a tongue and groove system and can be glued together for permanent installation or fixed using wood screws for a semi-permanent solution. The Harlequin Flexity panels are laid in such a way that cross joins do not coincide. This provides consistent shock dampening across the floor and offers the same feel and energy return to one or several dancers.

## **Specification Guide**

opeomodion edide	
Permanent or Portable	Permanent or Semi-Permanent
Panel Size	1.125m x 2.250m
Dance Surface Area	1.089m x 2.214m
Minimum Floor Thickness (before inclusion of chosen surface)	37mm
Weight	11.85kg/m² (Without surface)
Testing Standard	BS EN 14904:2006
Shock Absorption	67%
Vertical Deformation	3.9mm
Area Deflection	12.8%
Rolling Load	>1500 N
Testing Standard	BS EN 1991-1-1:2002
Point Load	>3.60kN
Uniform Distributed Load	>10.00kN
Fire Rating	Bfls 1 to EN 13501
Impact Generated Sound Level within room (Lw)	104.20 dB
Thermal Resistance - R Value	1.52 m <sup>2</sup> K/W
Thermal Insulation - U Value	0.658 W/m <sup>2</sup> K
Category of Use	A4
VOC Emissions	<0.10 mg/m <sup>3</sup>
Warranty	10 years if installed by Harlequin
	5 years if installed by the customer
Installation	Installed by Harlequin or for self- installation
Underfloor Heating	Suitable for use with underfloor heating





Birch plywood stained black

Single density pads







If you would like further information or advice please contact us on +342 46 44 22 or info@harlequinfloors.com

The Company reserves the right to make any variation in design or construction of the material described. Harlequin @ is a registered trademark of British Harlequin plc. @ Harlequin Floors 04/2024

