## Harlequin Clarity

**Harlequin Clarity** is a durable transparent vinyl performance floor with a slip-resistant embossed surface. It is ideal for reverse digital printing, where the printed design is on the underside of the floor and therefore protected from wear and damage.

**Installation:** Harlequin Clarity is specified for permanent or temporary installation. For permanent installation the joins are cold welded and for temporary installation double sided tape is used to form a continuous performance surface.

**Usage:** When reverse printed, Harlequin Clarity is suitable for high-traffic commercial use and as a dance surface. It can also be used as a clear protective wear layer which allows the floor underneath to show through or it can be used to protect an existing floor, such as a floor in a listed building.

## **Specification Guide**

·	
Material	Homogeneous vinyl
Permanent or Portable	Both
Roll Length	15m
Roll Width	1.52m
Maximum Printed Area	1.47m x 14.24m
Thickness	1.90mm
Weight	2.47kg/m <sup>2</sup>
Finish	Embossed
Fire Rating	Cfl-s1 (EN 13501-1)
Warranty - Unprinted Flooring	10 years if installed by Harlequin
	5 years if installed by the customer
Warranty - Printed Flooring	The warranty period will depend upon the intended use.
Fixing Type	Adhesive or Tape
Seams	Cold Welded or Taped
Gloss Level	Nominal 6
Lightfastness	≥6
VOC Emissions	≤0.5mg/m³
Recyclability	100%
Underfloor Heating	Suitable for use with underfloor heating
Third Party Certification	Environmental Product Declaration A <sup>+</sup> LEED, BREEAM, REACH Compliant



000 - Clear







