
Harlequin Hi-Shine

Harlequin Hi-Shine has a unique scratch resistant, high-gloss surface which creates a striking glossy, reflective surface. It is a hard-wearing and reusable vinyl floor, ideal for touring.

Installation: Harlequin Hi-Shine is specified for temporary 'loose-lay' installation, the joins are taped to create a continuous performance surface. It can be rolled out on any flat, smooth surface. It rolls out quickly, lays flat and stays flat.

Usage: Harlequin Hi-Shine is widely used for concerts and touring bands, film and television sets, fashion shows, product launches, parties, exhibitions, museums, window displays, theatrical and operatic productions and many other events.




Specification Guide

opeomodition ourde	
Material	Heterogeneous vinyl
Permanent or Portable	Portable
Roll Lengths	Metallics & Colours - 10m, 15m, 20m, 30m Blue - 20m Red - 30m
Roll Width	1.5m
Thickness	1.5mm
Weight	1.96kg/m ²
Finish	Smooth
Fire Rating	Bfl-s1 (EN 13501-1)
Warranty	2 years
Impact Sound Reduction	ЗdВ
Fixing Type	Таре
Seams	Taped
Gloss Level	High gloss
Lightfastness	≥6
Recycled Content	23-30%
VOC Emissions	≤0.5mg/m³
Recyclability	100%
Underfloor Heating	Not suitable for use with underfloor heating
Third Party Certification	Environmental Product Declaration A ⁺ LEED, BREEAM, REACH Compliant



If you would like further information or advice please contact us on +352 46 44 22 or info@harlequinfloors.com

Made in the EU. The Company reserves the right to make any variation in design or construction of the material described. Harlequin® is a registered trademark of Harlequin Europe SA. © Harlequin Floors 09/2023





LONDON & LUXEMBOURG & BERLIN & MADRID & PARIS & LIEGE & PHILADELPHIA & LOS ANGELES & FORT WORTH & SYDNEY & HONG KONG & TOKYO