Harlequin Standfast

Harlequin Standfast is a durable multi-purpose homogeneous vinyl performance floor with a slip-resistant surface. It is is an ideal heavy-duty floor for studios as well as stage flooring for dance studios and theatres.

Installation: Harlequin Standfast is specified for permanent installation, the joins are heat welded to form a continuous performance surface. It can be laid on any hard, smooth subfloor and is an excellent choice as a vinyl performance surface in conjunction with a Harlequin sprung floor.

Usage: Harlequin Standfast is suitable for theatre, drama and many genres of dance including percussive dance (flamenco, Irish and tap), hip-hop, jazz, street and Zumba. It is also ideal as a multi-use stage floor.

Specification Guide

| Material | Homogeneous vinyl |
|---------------------------|---|
| Permanent or Portable | Permanent |
| Roll Lengths | 10m, 15m, 20m |
| Roll Width | 1.5m |
| Thickness | 2.6mm |
| Weight | 3.4kg/m² |
| Finish | Smooth |
| Fire Rating | Cfl-s1 (EN 13501-1) |
| Warranty | 10 years if installed by Harlequin |
| | 5 years if installed by the customer |
| Impact Sound Reduction | 3dB |
| Fixing Type | Adhesive |
| Seams | Welded |
| Light Reflectance | 406-8, 501-2, 004-28 |
| Gloss Level | Nominal 6 |
| Lightfastness | >6 |
| Recycled Content | 23-30% |
| VOC Emissions | ≤0.5mg/m³ |
| Recyclability | 100% |
| Underfloor Heating | Suitable for use with underfloor heating |
| Third Party Certification | Environmental Product Declaration A ⁺ LEED, BREEAM, REACH Compliant |





Grey - 004



Black - 501

















