Harlequin Liberty HD


Harlequin Liberty HD is a development of our renowned Liberty sprung floor panel system, designed with enhanced durability in mind for more challenging environments. Harlequin Liberty HD is a birch plywood sprung floor panel system featuring shock dampening dual-density elastomer pads. The panels are coated with a black polymer resin, with a textured, high-grip pattern on the top surface which is high-wear, slip-resistant and weatherproof. The panels join using a rounded tongue and groove and are secured in place using our proprietary 'one turn of the key' latch and lock mechanism. Harlequin Liberty HD provides consistent shock dampening across the floor and offers the same feel and energy return to one or several dancers.

Performance surface: Harlequin Liberty HD can be used with a variety of Harlequin performance vinyls. Edge trims and ramps are available if required. For easy storage and transportation please see Harlequin's panel cart.

Installation: Harlequin Liberty HD is designed for both permanent or portable installation. The panels are laid in a 'brickwork fashion' onto the sub-floor so that cross joins do not coincide.

Specification Guide

| Specification Guide | |
|--|---|
| Permanent or Portable | Both |
| Panel Size | 2m x 1m & 1m x1m |
| Minimum Floor Thickness (exclusive chosen surface) | 37mm |
| Weight | 12.5kg/m² (Without surface) |
| Testing Standard | BS EN 14904:2006 |
| Shock Absorption | 67% |
| Vertical Deformation | 4.1mm |
| Area Deflection | 12.8% |
| Rolling Load | >1500 N |
| Testing Standard | BS EN 1991-1-1:2002 |
| Point Load | >3.60kN |
| Uniform Distributed Load | >10.00kN |
| Fire Rating | Bfl-s1 to EN 13501 |
| Impact Generated Sound Level within room (Lw) | 104.20dB |
| Thermal Resistance - R Value | 1.52 m ² K/W |
| Thermal Insulation - U Value | 0.658 W/m ² K |
| Category of Use | A4 |
| VOC Emissions | <0.10 mg/m ³ |
| Warranty | 10 years, 5 years if not installed by Harlequin |
| Installation | Installed by Harlequin or the customer |
| Underfloor Heating | Suitable for use with underfloor heating |









performance vinyl

Harlequin's 'latch and lock' system







If you would like further information or advice please contact us on +352 46 44 22 or info@harlequinfloors.com

Made in the EU. The Company reserves the right to make any variation in design or construction of the material described. Harlequin® is a registered trademark of Harlequin Europe SA. n Harlequin Floors 07/2023

