

## CARE AND MAINTENANCE INSTRUCTIONS HARLEQUIN ROCKSURE

### Entrance Matting

The first line of defence in protecting your flooring is to have effective barrier mats at the entrance to any floorings. An effective matting will significantly reduce the amount of wet and dry soiling being carried on the underside of footwear.

To be effective we would strongly recommend the length of the matting should be at least 2 to 3 footfalls, and it should be regularly vacuumed and cleaned.

Limiting foot borne contamination will make your daily maintenance regime easier.

The recommended maintenance instructions must be adhered to so as to ensure that the floor covering retain its appearance for longer and most important not impair its performance and aesthetics.

### Initial Maintenance / New Installation

Sweep the floor covering with a soft broom or dust control mop to remove any loose dirt, debris and dust.

Damp mop the floor using a diluted solution of Harlequin Vinyl Daily Floor Cleaner in the ratio of 1:25, 200 ml of Vinyl Dance Floor Cleaner to 5 litres of clean warm water.

Follow up by rinsing the floor with a damp not wet mop. Avoid saturation of the floor.

Allow the floor to dry, before use.

### Daily Maintenance

Sweep the floor covering with a soft broom or dust control mop to remove any loose dirt, debris and dust.

Damp mop the floor using a diluted solution of Harlequin Vinyl Daily Floor Cleaner in the ratio of 1:50, 100 ml of Daily Floor Cleaner in 5 litres of warm water.

Follow up by rinsing the floor with a damp not wet mop. Avoid saturation of the floor.

Allow the floor to dry before use.



## CARE AND MAINTENANCE INSTRUCTIONS HARLEQUIN ROCKSURE

### Floor Care Best Practice

Always protect by covering newly installed floors, when other trades are operating.

Regular cleaning is more effective and will retain the performance of the product longer than if occasional 'deep clean' is adopted.

The frequency of cleaning and type of maintenance adopted is dependent on the frequency of use, the degree of soiling and the level of hygiene standard required.

Always use Harlequin recommended floor cleaning products and to the dilution rates recommended. Improper use will have an adverse effect on the floor covering, leading to both damage of the surface and potential shrinkage and staining/discolouration of the floor covering. Permanent damage cannot be reversed.

Abrasive powders/creams, strong solvents such as Acetone or highly alkaline solutions should not be used as they will do irreversible damage to the floor.

The floor should not be exposed to any bare metal with sharp edges as it will damage the floor.

Any liquid spills must be cleaned as soon as possible.

Ideal ambient conditions are 50% RH (relative humidity) at a nominal temperature of 25oC.

